

## Electrochemical Behavior of Supercapacitor Electrodes Based on Activated Carbon and Fly Ash

S. Martinović<sup>1</sup>, M. Vlahović<sup>1</sup>, E. Ponomaryova<sup>2</sup>, I.V. Ryzhkov<sup>2</sup>, M. Jovanović<sup>3</sup>, I. Bušatlić<sup>3</sup>, T. Volkov Husović<sup>4</sup>, Z. Stević<sup>5,\*</sup>

<sup>1</sup> University of Belgrade, Institute of Chemistry, Technology and Metallurgy, Belgrade, Serbia

<sup>2</sup> Prydniprovsk State Academy of Civil Engineering and Architecture, Dnipropetrovsk, Ukraine

<sup>3</sup> University of Zenica, Faculty of Metallurgy and Material Science, Zenica, Bosnia and Herzegovina

<sup>4</sup> University of Belgrade, Faculty of Technology and Metallurgy, Belgrade, Serbia

<sup>5</sup> University of Belgrade, Technical Faculty in Bor, Bor, Serbia

\* E-mail: [zstevic@tfbor.bg.ac.rs](mailto:zstevic@tfbor.bg.ac.rs)

doi: 10.20964/2017.08.63

Received: 19 January 2017 / Accepted: 8 June 2017 / Published: 12 July 2017

---

The possibility of applying fly ash from power plants as a binder in supercapacitor electrodes based on activated carbon was investigated in this research. Based on the mechanical and electrical properties of the electrodes, the optimal ratio between fly ash and AC was determined. Supercapacitor electrodes were prepared in two ways: by pressing and by laser solidification. The preparation method significantly affected physical properties of the electrodes as well as the electrochemical behavior in supercapacitor setup. The electrodes were electrochemically tested by galvanostatic and potentiostatic methods and cyclic voltammetry. In order to improve the estimation of supercapacitor parameters, mathematical model that perfectly describes the behavior of investigated electrodes in aqueous solution of sodium nitrate was developed. The best results were obtained with laser-solidified electrode in 1M aqueous solution of NaNO<sub>3</sub>. Specific capacitance of 105 F/g, serial resistance of 0.57 Ω and self-discharge resistance of 95 Ω were achieved. Stability at high number of cycles proved to be very good. After 2000 cycles of CV at scan rate of 100 mV/s, specific capacitance fell by only 4.6 %.

---

**Keywords:** supercapacitors; activated carbon; fly ash; laser solidification; NaNO<sub>3</sub>

[FULL TEXT](#)

© 2017 The Authors. Published by ESG ([www.electrochemsci.org](http://www.electrochemsci.org)). This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution license (<http://creativecommons.org/licenses/by/4.0/>).